



FORMULA FIVE

INDUSTRIAL BUTYL CLEANER

Industrial Butyl Cleaner. Butyl fortified positive emulsion cleaner - for the tough jobs

SPECIFICATIONS

- Appearance: Clear, purple liquid
- Odor: Solvent
- Density: 8.68
- pH: 13.5/11.8
- Refractive index: 1.3505
- Hard water tolerance: >3200 ppm
- Solvent %: 5%
- Flashpoint: None
- USDA rating: A-1
- Foam generation: Moderate
- Stability: Stable
- Freeze/thaw stability: OK 3 cycles
- Shelf life: 1 year minimum

FEATURES AND BENEFITS

- Positive emulsion
- Balanced builder blend

TARGET SURFACES

- Industrial heavy duty maintenance cleaner
- Floors
- Walls
- Machinery
- Systems through mechanical cleaning devices
- Dip-tank application



Available in 4X1 gallon cases and 55 gallon drums

DIRECTIONS

- Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Divide floor into workable sections
- Dilute Formula One with water as follows:
 - Super heavy soils: 1:1 (64 oz per gallon)
 - Heavy soil: 10:1 (13 oz per gallon)
 - Moderate soil: 12:1 (10 oz per gallon)
- Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an autoscrubber
- Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area
- For pressure cleaning draw concentrate directly from container. Set dilution using pressure washer manufacturer's directions according to soil present



NUANCE
SOLUTIONS