

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product code : 1571ABS

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleansing product

1.3. Supplier

Nuance Solutions
900 E 103rd Street
Suite D
Chicago, IL
United States
T 773-785-2300
regulatory@nuancesolutions.com - www.nuancesolutions.com

1.4. Emergency telephone number

Emergency number : 1-800-535-5053
For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
Within USA and Canada: 1-800-535-5053
Outside USA and Canada: 011-1-352-323-3500
(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Hazardous to the aquatic environment - Acute Hazard Category 3	H402	Harmful to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H402 - Harmful to aquatic life

Precautionary statements (GHS US) :

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor

P321 - Specific treatment (see supplemental first aid instruction on this label)
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local regulations

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
ETHANOLAMINE	CAS-No.: 141-43-5	5 – 10
ALKYL (C10-C16) BENZENESULFONIC ACID	CAS-No.: 68584-22-5	5.4 – 6
TETRASODIUM EDTA	CAS-No.: 64-02-8	2.96 – 3.12
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5
SODIUM LAURETH SULFATE	CAS-No.: 68585-34-2	0.746 – 1.119
SULFURIC ACID	CAS-No.: 7664-93-9	0.06 – 0.18

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/vapours/spray.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DYNA-FOAM	
No additional information available	
SODIUM LAURETH SULFATE (68585-34-2)	
No additional information available	
ALKYL (C10-C16) BENZENESULFONIC ACID (68584-22-5)	
No additional information available	
SULFURIC ACID (7664-93-9)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.2 mg/m ³ (Thoracic fraction)
SODIUM XYLENE SULFONATE (1300-72-7)	
No additional information available	
ETHANOLAMINE (141-43-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm
Remark (ACGIH)	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	Ethanolamine
OSHA PEL (TWA) [1]	6 mg/m ³
OSHA PEL (TWA) [2]	3 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TETRASODIUM EDTA (64-02-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: red
Odor	: Odourless
Odor threshold	: No data available
pH	: 11 – 11.6
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ALKYL (C10-C16) BENZENESULFONIC ACID (68584-22-5)

LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	--

LC50 inhalation rat (mg/l)	> 1.9 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
----------------------------	---

SULFURIC ACID (7664-93-9)

LD50 oral rat	2140 mg/kg body weight (Rat, Experimental value, Oral)
---------------	--

ATE US (oral)	2140 mg/kg body weight
---------------	------------------------

SODIUM XYLENE SULFONATE (1300-72-7)

LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
---------------	--

LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))
--------------------	--

ETHANOLAMINE (141-43-5)

LD50 oral rat	1515 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
---------------	--

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHANOLAMINE (141-43-5)	
LD50 dermal rabbit	2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 week(s), Rabbit, Male / female, Experimental value, Dermal)
ATE US (oral)	1515 mg/kg body weight
ATE US (dermal)	1018 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

TETRASODIUM EDTA (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
Skin corrosion/irritation	: Causes severe skin burns. pH: 11 – 11.6
Serious eye damage/irritation	: Causes serious eye damage. pH: 11 – 11.6
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

SULFURIC ACID (7664-93-9)	
National Toxicity Program (NTP) Status	Known Human Carcinogens
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

ALKYL (C10-C16) BENZENESULFONIC ACID (68584-22-5)	
NOAEL (oral,rat,90 days)	500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

ETHANOLAMINE (141-43-5)	
NOAEL (oral,rat,90 days)	300 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline 416 (Two-generation reproduction toxicity study)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

SULFURIC ACID (7664-93-9)	
LC50 - Fish [1]	42 mg/l (96 h, Gambusia affinis)
EC50 - Daphnia [1]	29 mg/l (24 h, Daphnia magna)

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM XYLENE SULFONATE (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

ETHANOLAMINE (141-43-5)	
LC50 - Fish [1]	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Daphnia [1]	65 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	0.85 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	1.24 mg/l Test organisms (species): Oryzias latipes Duration: '41 d'

TETRASODIUM EDTA (64-02-8)	
LC50 - Fish [1]	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 - Daphnia [1]	625 mg/l (24 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

SULFURIC ACID (7664-93-9)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

SODIUM XYLENE SULFONATE (1300-72-7)	
Persistence and degradability	Readily biodegradable in water.

ETHANOLAMINE (141-43-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance
BOD (% of ThOD)	0.32

TETRASODIUM EDTA (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O ₂ /g substance

12.3. Bioaccumulative potential

SULFURIC ACID (7664-93-9)	
Partition coefficient n-octanol/water (Log Pow)	-2.2 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM XYLENE SULFONATE (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.
ETHANOLAMINE (141-43-5)	
BCF - Other aquatic organisms [1]	2.3 – 9.2 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.
TETRASODIUM EDTA (64-02-8)	
Partition coefficient n-octanol/water (Log Pow)	-2.6
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

SODIUM XYLENE SULFONATE (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.
ETHANOLAMINE (141-43-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.16 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.4. Packing group

Packing group (DOT) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

SULFURIC ACID (7664-93-9)

CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

15.2. International regulations

SULFURIC ACID (7664-93-9)

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.


DYNA-FOAM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : X - Special handling directions

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.